



\*SPACER BODY LENGTH IS ORDERED BY DISTANCE BETWEEN SHAFT ENDS (DBSE) SPACER BODY SHORTENED BY THE "E" DIMENSION AT THE FACTORY

\*A-SERIES FLANGES ARE THE STANDARD FLANGE FOR MILLENNIUM SPACER COUPLINGS

**DIMENSIONS (IN INCHES) FOR Millennium® SPACER COUPLINGS**

SIZE	M00	M0	M1	M2	M3	M4	M5	M6	M7	M8	M9	M10	M11	M12
EXTERNAL D1	2.170	2.840	3.860	4.820	5.750	7.600	9.700	11.800	13.600	15.460	17.860	19.875	23.030	27.600
MAXIMUM BORE HUB	1.000	1.375	1.750	2.250	2.500	3.375	4.500	5.500	6.000	7.250	9.000	10.000	11.000	13.250
MAXIMUM BORE FLANGE HUB	0.875	1.375	1.875	2.250	2.875	3.375	4.000	5.000	5.750	7.125	8.250	10.500	11.000	14.250
*MAX BORE HEAVY DUTY FLANGE						3.875*	5.000*	6.875*	7.125*	8.875*	9.250*	11.875*		
PILOT BORE d1	0.250	0.300	0.500	0.609	0.750	0.940	1.000	1.500	1.750	2.450	2.900	3.750	N/A	4.000
L1	0.965	1.375	1.700	2.200	2.450	3.200	4.450	5.440	5.940	7.190	8.940	9.940	N/A	11.450
L2	1.025	1.438	1.620	2.125	2.411	2.610	3.410	4.312	4.625	7.00	9.100	11.100	9.812	11.625
D2	1.600	2.200	2.875	3.500	4.000	5.500	6.500	8.000	9.000	10.500	12.000	14.000	N/A	18.500
D3	1.700	2.400	3.150	3.900	4.900	6.400	8.180	9.930	11.800	13.940	15.900	17.870	19.650	23.850
D4	2.500	3.415	3.940	4.710	5.515	6.950	8.860	10.000	10.490	12.800	15.087	19.000	17.900	23.900
D5 (HEAVY DUTY FLANGE USE D4)	1.350	2.280	2.358	3.500	4.200	5.00	6.625	7.250	8.275	10.000	11.875	13.000	14.000	18.000
J1	1.088	1.375	1.562	1.940	2.315	2.548	3.350	4.250	4.500	7.000	9.000	11.000	9.750	11.500
J2	1.000	1.375	1.750	2.250	2.500	3.250	4.500	5.500	6.000	7.250	9.000	10.000	11.00	11.500
F	0.035	0.035	0.050	0.050	0.050	0.050	0.060	0.060	0.060	0.060	0.060	0.060		0.060
H	0.020	0.020	0.060	0.060	0.060	0.060	0.060	0.060	0.060	0.100	0.100	0.100	0.125	0.125
K	0.720	1.145	1.570	1.600	2.150	3.100	3.500	3.900	5.150	6.280	6.530	6.650	N/A	9.200
E (GAP)	.062	.075	.075	.075	.075	.200	.200	.200	.200	.200	.200	.250	N/A	.250
STANDARD BODY LENGTH	3.5	3.0 3.5	3.0 3.5 3.75 4.0 4.5 5.0	3.0 3.5 3.75 4.0 5.0 5.5 7.0	3.5 3.75 5.0 5.25 5.5 7.0 7.25 7.5	4.0 5.0 6.0 7.0 9.5 10.0 12.0	5.0 6.0 7.0 7.25 9.75 10.0 12.0		7.0 TO 14.0	7.0 TO 18.0	7.5 TO 18.0	9.5 TO 20.0	9.5 TO 20.0	12.0 TO 24.0

CUSTOM LENGTHS AVAILABLE WITH EXTRA CHARGE

DROP OUT SPACER COUPLINGS TO CONVERT YOUR GREASE LUBRICATED GRID SPACER COUPLING TO A LOW MAINTENANCE ATRA-FLEX COUPLING AVAILABLE

NOTE: Use Table 2 (page 4) Horsepower Capacity at Various RPM.