



SAE FLYWHEEL COUPLING DIMENSIONS (IN INCHES) FOR Millennium

SIZE	D1	D2	D3	d1	d2	E	L4	G	H	I	MAX BORE	MAX RPM W/O BALANCING
M4	7.600	5.500	6.400	0.500	0.050	0.200	0.375	5.725	3.250	2.275	3.375	3000
M5	9.700	6.500	8.180	0.090	0.060	0.200	0.375	6.815	4.500	2.115	4.500	2500
M6	11.800	8.000	9.930	0.600	.060	0.200	0.625	8.875	5.550	3.125	5.500	2100
M7	13.260	9.000	11.900	1.000	0.060	0.200	0.750	10.450	6.000	4.250	6.000	1800
M8	15.460	10.500	13.900	1.500	0.060	0.200	0.750	12.700	7.250	5.250	7.250	1500
M9	17.860	12.000	15.900	1.500	0.060	0.200	1.000	14.825	9.000	5.625	9.000	1300
M10	19.875	14.000	17.900	1.250	0.060	0.200	1.250	16.000	10.000	5.750	10.000	1000
M12	27.600	18.500	23.900	1.500	0.060	0.250	1.250	20.750	13.250	7.250	13.250	900

FLYWHEEL DIMENSIONS FOR STANDARD CLUTCH DIAMETERS

SAE	6.5	7.5	8	10	11.5	14	16	18	21	24
D5	8.500	9.500	10.375	12.375	13.875	18.375	20.375	22.500	26.500	28.875
BC	7.875	8.750	9.625	11.625	13.125	17.250	19.250	21.375	25.250	27.250
L4	.3125	.3125	.375	.375	.375	.375	.625	.750	.750	.750
CH	.3281	.3281	.3906	.3906	.3906	.5156	.5156	.6406	.6406	.7656
CHX	6	8	6	8	8	8	8	6	12	12

*Factory recommends a service factor of 3.0 to 4.0

**Refer to horsepower capacity at various RPM on page 4 for Millennium®

***Consult factory for custom sizes